

Introducing the new
FX-20 & FX-30

HAY - HOPS - HEMP - BRAZIL NUTS - TOBACCO - DATES



The next generation of moisture meters is here, with the introduction of the **Navigator™** series and **EDGE™** app from Delmhorst.

NEW FX-20 AND FX-30

The **FX-20** and **FX-30** are the latest in the new Navigator family of moisture meters from Delmhorst. Uniquely designed for use in the field with a dashboard-like display that is easy to read, and large, easy to use navigation buttons.

The **FX-20** Hay meter is perfect for large and small volume producers to ensure reliable %MC readings in the windrow or in all size bale packages. Accurate moisture monitoring is essential to reduce mold development, preserve leaves, color and feed value. The FX-20 can be used with various existing Delmhorst hay prods and accessories.

The **FX-30** multi-purpose meter features the Delmhorst **EDGE™** app with customizable settings and user-selectable calibrations for **Hay, Hops, Hemp, Brazil Nuts, Tobacco, and Dates**. Having a reliable, accurate tool to monitor moisture through each phase of the process enhances quality control and increases profits.



Product Features

- Large, custom display with auto backlight – easy to read under all conditions
- Modern case design with large, tactile buttons and E-Z grip handle
- On-screen statistics for up to 100 readings saved to the meter - High, Low, Average, Standard Deviation
- Moisture Range:
 - FX-20: Hay 6%-40%
 - FX-30:
 - Hay - 6%-40%
 - Hops - 8%-23%
 - Hemp – 7%-34%
 - Tobacco – 8%-37%
 - Brazil Nuts – 6%-25%
 - Dates – 6%-25%
- Temperature correction (°F / °C - FX-30 only)
- Bluetooth® connectivity (FX-30)
- Color-coded LED's – adjustable through **EDGE™** app (FX-30)
- Alarm set point - alerts to user-selected MC level
- Internal calibration check
- "Low Batt" warning with audio
- Auto off timer. Set to 1m, 4m or 10m
- Compatible with existing Delmhorst prods and electrodes

The Delmhorst **EDGE™** app offers:

- Timestamp and geotag
- Data export to .csv format
- Save unlimited readings
- Customized LED ranges

Meter Specifications

- Power: 2x AA Alkaline batteries
- Op Temp: 0°-255°F (-18°-124°C)
- QR code on meter for easy access to support materials and meter registration
- Size: meter only - 8.03in x 2.85in x 1.60in (20.40cm x 7.24cm x 4.06cm)
- Weight: meter only - 7.7oz (218gm)
- Optional hard plastic carrying case
- 2-year limited warranty on manufacture's defects. Bonus warranty with on-line registration

Typical packages:

HAY – FX-20 or FX-30 with assorted available prods – see <https://www.delmhorst.com/moisture-meters/agriculture>

HOPS – FX-30 with H-4 handle and 830-5 12in prod and/or 2-E electrode

HEMP – FX-30 with H-4 handle and 830-2 10in or 830-3 18in prod and/or 2-E electrode

TOBACCO – FX-30 with H-4 handle, 830-2 10in prod and/or 37-EC multipin electrode

BRAZIL NUTS – FX-30 with 2-E electrode

DATES – FX-30 with 2-E electrode

Optional carrying case (324CAS-0112) is available with any of the above available

Electrodes and prods are interchangeable. Others are available to accommodate most applications.

Contact us or visit our website for more information.