

Introducing the new  
**HTX-30**  
THERMO-HYGROMETER



The next generation of thermo-hygrometer is here, with the introduction of the **Navigator™** Series and **EDGE™** app from Delmhorst.

# The New HTX-30

The **HTX-30 all-purpose Thermo-Hygrometer** is the latest product from the Delmhorst® Navigator® meter family. The hand-held HTX-30 has a quick response time, simple interface and provides useful statistics, making it the ideal tool for measuring air conditions in water damage restoration, building inspections, flooring installations and many other industrial and research applications.

The HTX-30 measures Temperature and Relative Humidity. **The meter calculates Vapor Pressure, Dewpoint, and Mixing Ratio.** Through Bluetooth®, the HTX-30 can connect to the **EDGE™** app and share saved readings for further analysis. The HTX-30 makes the most challenging projects easier, less costly, and more efficient.

## Product Features

- Large, custom display with auto backlight – easy to read under all conditions
- Modern case design with large, tactile buttons and E-Z grip handle
- On-screen statistics for up to 500 readings saved to the meter - High, Low, Average
- **Measures:**
  - Relative Humidity (%RH)
  - Temperature (°F / °C)
- **Calculates**
  - Vapor Pressure (PSI, kPa)
  - Mixing Ratio (GPP, GPK)
  - Dewpoint (°F / °C)
- Bluetooth® connectivity
- Set Location Number (1-30)
- "Low Batt" warning with audio
- Auto timer. Set to 1m, 4m, 10m

## Meter Specifications

- Power: 2X AA Alkaline batteries
- Op Temp: 02-255°F (-18-124°C)
- QR code on meter for easy access to support materials and meter registration
- Size: meter only - 7.9in x 2.9in x 1.6in (20.07cm x 7.36cm x 4.06cm)
- Weight: meter only - 7.3oz (207gm)
- Hard plastic carrying case included
- (1) RH/T-XE sensor included
- 2-year warranty on manufacturer's defects. Bonus warranty with on-line registration

## The Delmhorst **EDGE™** app offers:

- Timestamp and geotag
- Data export to .csv format
- Save unlimited readings
- Add notes to each location
- Designate readings to a location/room or dehumidifier
- View and filter all readings



### **RH/T-XE Extended Sensor**

Detachable, extended length sensor (2.5 in) for measuring Relative Humidity and Temperature. Useful for determining the psychrometric conditions in the output of dehumidifiers or other recessed areas. Order individually or in packs of 5.



### **RH/T-C2 Extension Cable**

3 foot long extension cable that connects the HTX-30 to the RH/T-XE allowing users to view their meter screen while taking measurements in hard-to-reach areas.